



Agip FORMULA MOTO GEAR 80W-90

AGIP GEAR is a gear oil based on mineral oil for the lubrication of bike gears and variable automatic gears.

Characteristics (typical figures):

Agip GEAR	Unit	80W-90	Test method	
Kin. Viscosity	at -26°C	mPa.s	150.000	DIN 51 550
	at 40°C	mm ² /s	130	
	at 100°C	mm ² /s	15,4	ASTM D 445
Viscosity index		110	DIN ISO 2909	
Density at 15°C	kg/m ³	897	ASTM D 1298	
Flashpoint o. C.	°C	200	ASTM D 92	
Pour point	°C	-24	ASTM D 97	

Properties and Performance:

Agip GEAR oils are produced from base oils that already have a good viscosity-temperature-behaviour. Special additives improve the flow behaviour at low temperatures, which enables the application over a broad temperature range. At low temperatures the lower inner friction causes next to a reduction of wear smaller performance losses and therefore minimizes the fuel consumption.

Applications:

Agip GEAR can be used for the lubrication of bike gears under all climatic conditions. Among other things it is also used for the lubrication of variable automatic gears e. g. at scooter. For this it is also approved by name by Piaggio.

Please observe the manufacturer's specifications when selecting products.

Specifications:

Agip GEAR is approved by name respectively meets the requirements* of the following specifications:

API GL-4
Piaggio-Group